



| Product name   |                                     | Production location  |  |
|--|-------------------------------------|--|--|
| Gera (With Chamfered Edge, without spacers)  | NPD                                 | Oberlausitz  |  |
| Format   |                                     |  |  |
| Moulding method  |                                     | Wirecut  |  |
| KF52: 200 x 100 x 52 mm  |                                     | Between batches the average size and color may slightly differ.  |  |
| Essential Characteristics - EN1344   |                                     |  |  |
|   |                                     |  |  |
| Reaction to fire   | A1                                  |  |  |
| External fire performance  | NPD                                 |  |  |
| Dangerous substances   | NPD                                 |  |  |
| Transverse breaking load   | T4                                  | Category   |  |
| Unpolished slip/skid resistance USRV   | U3                                  | Category   |  |
| Thermal conductivity   | NPD                                 |  |  |
| Durability against freeze thaw   | FP100                               | Category   |  |
| Sustainable slip/skid resistance   | NPD                                 | Category   |  |
| Other Characteristics - EN1344 & BRL 2360  |                                     |  |  |
| Paver quality 1  | NPD                                 | Category   |  |
| Paver quality 1 Tolerances   | $\leq 0,4 \sqrt{\text{dimensions}}$ |  |  |
| Paver quality 1 Range  | R1                                  | Category   |  |
| Water absorption   | $\leq 6\% \text{ m/md}$             |  |  |
| Abrasion resistance  | NPD                                 | Category   |  |
| Acid resistance  | NPD                                 | Category   |  |
| Other Characteristics - PTV 910  |                                     |  |  |
| Standardized Quality Classes   | NPD                                 |  |  |
| Water absorption   | W2 ( $\leq 5\%, \leq 6\%$ )         |  |  |
|    |                                     |  |  |
| Storage & handling   |                                     | Cutting  |  |
| <ul style="list-style-type: none"> <li>- Stock pavers on a clean surface and cover them</li> <li>- Blend from different pavers (pack) at the same time</li> <li>- Do not clean fresh masonry with hydrochloric acid</li> </ul> |                                     | Cutting with power tools may generate dust. This dust may contain silica or quartz particulate which may constitute a hazard. Persons undertaking work of this nature are advised to wear dust masks (FFP3). |  |